



**(D) Marine 180IB/50**

- Hoher Manipulationsschutz
- Individuell einstellbarer Code
- Bügelstärke 8 mm

**(F) Marine 180IB/50**


- Haute protection anti-manipulation
- Code interchangeable
- Diamètre anse 8 mm

**(NL) Marine 180IB/50**

- Hoge manipulatie weerstand
- Persoonlijk instelbare code
- Beugeldikte 8 mm

**(I) Marine 180IB/50**

- Alta resistenza all'attacco con destrezza
- Combinazione ricifrabile con codice personale
- Diametro arco 8 mm



180IB/50

a = 53 mm

b = 25 mm

c = 25 mm

d = 8 mm

180IB/50HB63

a = 53 mm

b = 25 mm

c = 63 mm

d = 8 mm

0000 1.



2.



4.

90°

3.

???? 5.

Code



6.

90°



7.



8.

**Merkmale - Caractéristiques - Kenmerken - Caratteristica**



(D) Individuell einstellbarer  
Zahlencode

(F) Code personnel,  
modifiable

(NL) Zelfinstelbare cijfercode

(I) Il codice può  
essere assegnato  
individualmente



(D) Doppelte Verriegelung

(F) Double verrouillage  
de l'anse

(NL) Beugel aan beide  
zijden vergrendeld

(I) Entrambe i lati  
dell'anello di trazione  
sono ben protetti

**Einsatzgebiete - Utilisation - Toepassingsmogelijkheden - Campo d'impiego**



**ABUS**  
D 58292 Wetter  
Germany

www.abus.com

180IB/50HB63 C/DENLI



4

003318

321177